



# SAFETY JOGGER

PROFESSIONAL



Light

## ATUM OB

ATUMOB

**Running-inspired occupational trainer with an ultra breathable mesh upper**

The ATUM OB from Safety Jogger is a stylish, lightweight shoe with a breathable upper and removable footbed. Perfect for assembly, logistics, medical and catering industries.

Upper	Knitted Textile
Lining	Textile
Footbed	SJ foam footbed
Outsole	TPR/EVA
Category	OB / SR, E
Size range	EU 35-48
Sample weight	0.338 kg
Norms	EN ISO 20347:2022+A1:2024



LGR



BLK



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### Slip resistance (SR)

Replaces the previously used term of SRA+SRB=SRC. SR means the slip test has been executed on tiles contaminated with soap and with oil.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

**SAFETY JOGGER**  
WORKS

**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Catering, Assembly, Logistics, Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Knitted Textile			
	Upper: permeability to water vapor	mg/cm²/h	63.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	509.2	≥ 15
Lining	Textile			
	Lining: permeability to water vapor	mg/cm²/h	11.7	≥ 2
	Lining: water vapor coefficient	mg/cm²	94.2	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	TPR/EVA			
	Outsole abrasion resistance (volume loss)	mm³	104.4	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.39	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.40	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.20	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.23	≥ 0.22
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	43	≥ 20

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com