



SAFETY JOGGER

INDUSTRIAL



Medium

BESTBOY252 S3

##

Safety Jogger BESTBOY252# ### ## ### ##### ##### #####
#####. ### ## ### ##### ## ## #####
#####.

## ##	## ##### ##
## ##	##
###	##
##	##
###	PU/##
Top	##
####	S3 / SR, CI, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.720 kg
###	ASTM F2413:2018 EN ISO 20345:2022



BLK



#####. 100##### 1## ##
##



#####.



#####.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ##, ##, ##, ###, ## # ##, ##

##:
##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ##### ##			
	##: ### ##	mg/cm²/h	2.2	≥ 0.8
	##: ### ##	mg/cm²	25.0	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	33.5	≥ 2
	##: ### ##	mg/cm²	269	≥ 20
###	##			
	###: ####(##/##)(###)	##	25600/12800	25600/12800
###	PU/##			
	### #####(## ##)	mm³	135	≤ 150
	### ## ## SRA: ###	##	0.40	≥ 0.28
	## SRA# ### ##: ##	##	0.40	≥ 0.32
	### ## ## SRB: ###	##	0.20	≥ 0.13
	## SRB# ### ##: ##	##	0.18	≥ 0.18
	### ## #	###	621	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	31	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	16.5	≥ 14
	#### ## # (## # ## ## 15kN)	mm	19.0	≥ 14

##:
##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ## # #####.