

SAFETY JOGGER

INDUSTRIAL

Medium

BESTGIRL S3 LOW

BSTGRLS3LO

**2nd generation of Bestgirl for multipurpose applications.
Improved fitting and comfort with full leather upper**

With a breathable leather upper, steel protection, ESD compliance and superior slip resistance, this S3-certified safety shoe delivers serious protection. Perfect for all-around industrial use, the BESTGIRL shoes combine rugged safety with excellent value.

Upper	Full Grain Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, LG, ESD, CI, FO
Size range	EU 35-43
Sample weight	0.498 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



BLK



Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




Ladder Grip (LG)

Especially defined contour in the shank area of a safety shoe to provide additional safety while standing on ladders.



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

**SAFETY
JOGGER**
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

Industries:
Assembly, Automotive, Chemical, Industry, Logistics, Construction

Environments:
Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Full Grain Leather			
	Upper: permeability to water vapor	mg/cm²/h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	29.4	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm²/h	86.31	≥ 2
	Lining: water vapor coefficient	mg/cm²	691	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	29.9	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.42	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.46	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.21	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.24	≥ 0.22
	Antistatic value	MegaOhm	13.2	0.1 - 1000
	ESD value	MegaOhm	13	0.1 - 100
	Heel energy absorption	J	31	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	20.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com