

Light

CADOR <mark>S1 P</mark>

Sporty low-cut ESD safety shoe

Cador is a low-cut S1P safety shoe made of mesh, a slip resistant outsole that fulfills electrostatic discharge requirements and a steel toe cap and anti-penetration sole. Its main assets? Good quality in exchange for a competitive price. High wearing comfort – with optimum shock absorption in heel and forefoot that puts an end to aching feet at the end of the working day. And a sporty and fun design with fashionable color accents, making it an ideal fit for both men and women. Of course with the same quality standards that Safety Jogger always guarantees and that allow you to work in complete safety. Ideal for light applications in the automotive, construction, industrial, logistics and engineering sector

GRN

YFI

Upper	Mesh	
Lining	3D-Mesh	
Footbed	SJ foam footbed	BLU
Midsole	Steel	BLU
Outsole	PU/PU	
Тоесар	Steel	
Category	S1 P / SR, ESD, FO	
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315	
Sample weight	0.580 kg	
Norms	ASTM F2413:2018	

EN ISO 20345:2022



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.

SRC slip resistance



Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



3FIT

Electrostatic Discharge (ESD) ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



SJ Foam

DVIK

RED

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.

Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetating the outsole.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com

Industries:

Automotive, Construction, Food & beverages, Logistics, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm²/h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	41	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	61.1	≥ 2
	Lining: water vapor coefficient	mg/cm ²	490	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	59	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.24	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	73	0.1 - 100
	Heel energy absorption	J	24	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace



INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP