

Light

## CADOR S1P MID

CADORMID

**Durable Safety Shoe for Multiple Industries**

Safety Jogger's sporty mid-cut CADOR S1P MID safety shoes offer superior protection with a steel toe cap and midsole, S1P safety features, SR slip resistance, and ESD control. The textile upper adds comfort.

Upper	Mesh
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S1 P / SR, ESD, FO
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.609 kg
Norms	ASTM F2413:2018 EN ISO 20345:2022



GRY



### S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



### Airblaze technology

Moisture and temperature management system to provide optimum wearer comfort by keeping your feet dry and comfortable.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Assembly, Automotive, Food & beverages, Industry, Logistics

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Mesh			
	Upper: permeability to water vapor	mg/cm²/h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	41	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm²/h	61.1	≥ 2
	Lining: water vapor coefficient	mg/cm²	490	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm³	59	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.24	≥ 0.18
	Antistatic value	MegaOhm	8.1	0.1 - 1000
	ESD value	MegaOhm	73	0.1 - 100
	Heel energy absorption	J	24	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com