



# SAFETY JOGGER

## INDUSTRIAL



Medium

## DAKAR EH SB

DAKAR-EH

**EH-rated, fashionable safety shoe with extraordinary technical features**

The Safety Jogger DAKAR-EH safety shoes offer superior electric shock resistance, slip resistance, and breathable comfort. Ideal for diverse work environments and industries.

Upper	Crazy Horse Leather, Textile
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Nano Carbon
Category	SB / P, SRC, E, FO, EH
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
Sample weight	0.670 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



019




018



### Electrical hazard (EH)

Electrical hazard (EH) rated safety shoes have nonconductive outsoles. As a secondary source of protection they reduce the potential for electric shocks under dry conditions.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### Nano carbon toecap

Ultralight high-tech material, metal-free with no thermal or electrical conductivity.



**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED  
IN EUROPE**

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Automotive, Construction, Logistics, Oil & Gas, Industry

Environments:

Muddy environment, Dry environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Crazy Horse Leather, Textile</b>			
	Upper: permeability to water vapor	mg/cm²/h	7.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	64	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	51.9	≥ 2
	Lining: water vapor coefficient	mg/cm²	415.5	≥ 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	145	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
Toecap	<b>Nano Carbon</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	17.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com