



SAFETY JOGGER

INDUSTRIAL

ECOLOBI S1P LOW TLS S1 PS

ECOLBIS1PT


####

ESD #### ##### ###### ##### ###### ##### ###### ##### ###### ##### ###### ##### ###### #####
#####


## ##	#####, ### ##
## ##	### ##
###	SJ ### # ###
##	## ## ##
## ##	######
Top	##
####	S1 PS / SR, ESD, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.535 kg
## ##	ASTM F2413:2018 EN ISO 20345:2022



TLS(##### ######)
Safety Jogger # ##### TLS ####
#####. ####
#####, #### #####
#####. #### ##### TLS ##### #####
#####. ####
#####.



####. #### #### #### #### #### #### #
-



####, #### # ####, ##
####, ##, ## # #### ##
####



####.



#####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

**ENGINEERED
IN EUROPE**

www.safetyjogger.com

##:
#####, ####, ##, ##

##:
##, ###

##:

##	## ##	##	EN ISO 20345
## ##	#####, ## ##		
	##: ## ##	mg/cm²/h	1.2
	##. ## ##	mg/cm²	≥ 0.8 21 ≥ 15
## ##	## ##		
	##: ## ##	mg/cm²/h	34.59
	##. ## ##	mg/cm²	≥ 2 277 ≥ 20
###	SJ #### # ##		
	##: #####(## ##)(##)	##	Dry 25600 cycles/Wet 12800 cycles 25600/12800
###	## ##/##		
	##: #####(## ##)	mm³	119.4mm³(Density:1.3)
	## ## ## - ## + NaLS - ## ## ##	##	≤ 150 0.48 ≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.48 ≥ 0.36
	SR ## ## - ## + ## - ## ## ## ##	##	0.36 ≥ 0.19
	SR ## ## - ## + ## - ## ## ##	##	0.36 ≥ 0.22
	## ## #	##	648 0.1 - 1000
	ESD #	##	19.4 0.1 - 100
	## ## ## ##	J	25 ≥ 20
Top	##		
	##: ## ## ## ## 100J	mm	NA
	##: ## ## ## ## 10kN	mm	N/A
	##: ## ## ## ## 200J	mm	15.5 ≥ 14
	##: ## ## ## ## 15kN	mm	22.0 ≥ 14

#

####. # # # ##### # #####. # # ##### # Safety Jogger # ##### #!, ##### # # ##### # ##### # ##### # ##### # #####.