


ECONILA S1 LOW

ECONILAS1L

#####

#####, ESD #####.
#####.


## ##	## ### ##
## ##	### ##
###	SJ ### # ###
##	N/A
###	###/###
Top	##
#####	S1 / SR, ESD, FO, HRO
## ##	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
## ##	0.429 kg
###	ASTM F2413:2018 EN ISO 20345:2022



```
###
## ### ### #####, ### # ###, ##
##### ## ###, ##, ## # ### ##
### ## ## # ### ## #### ## ##
### #####.
```



#####.



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## #
##### ## ##### ## #####.
```



```
### #(SR)
### ##### SRA+SRB=SRC ###
#####. SR# ### ##### ### ###
## ## ##### #####.

```



#####.



```
### ##
ESD# ## ### ##### # ## ###
##### ### ##### ##### ## ##
### #####. ## ### 100#####
100### #####.
```



BLK



KHA

##:
####, ###, ##, ##

##:
##, ### ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	2.3	≥ 0.8
	##: ### ##	mg/cm²	45	≥ 15
## ##	### ##			
	##: ### ##	mg/cm²/h	34.59	≥ 2
	##: ### ##	mg/cm²	277	≥ 20
###	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
###	###/##			
	### ####(## ##)	mm³	119.4mm³(Density:1.3)	≤ 150
	### ## ## SRA: ###	##	0.32	≥ 0.28
	## SRA# ### ##: ##	##	0.40	≥ 0.32
	### ## ## SRB: ###	##	0.18	≥ 0.13
	## SRB# ### ##: ##	##	0.21	≥ 0.18
	### ## #	###	215	0.1 - 1000
	ESD #	###	14.6	0.1 - 100
	#### ## ##	J	25	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	NA	N/A
	#### ## # (## # ## ## 10kN)	mm	NA	N/A
	#### ## # (## # ## ## 200J)	mm	16	≥ 14
	#### ## # (## # ## ## 15kN)	mm	17	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com