



# SAFETY JOGGER

INDUSTRIAL



Light

## FREEDOM S1PS MID

FYTS1PSMID

**Innovative and ultra-comfortable mid-cut safety shoe with an anatomically shaped toe cap for natural movement**

Free your toes with The FREEDOM S1PS MID. Engineered to move with you, the anatomically shaped toe cap supports your foot's natural biomechanics. Lightweight, breathable and entirely metal free, it features heel and forefoot energy absorption, ESD certification and a puncture-resistant midsole for all-day protection and comfort.

Upper	Textile
Lining	3D-Mesh
Footbed	SJ foam footbed
Midsole	Nonwoven
Outsole	ETPU/Rubber (NBR)
Toecap	Nano Carbon
Category	S1 PS / SR, SC, ESD, CI, FO
Size range	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
Sample weight	0.585 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024




### 3D mesh

Three-dimensional produced distance mesh to provide increased moisture and temperature management.



### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



### Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



BLK

SAFETY  
JOGGER  
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

Industries:

Assembly, Automotive, Industry, Logistics

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Textile			
	Upper: permeability to water vapor	mg/cm² /h	32.71	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	262	≥ 15
Lining	3D-Mesh			
	Lining: permeability to water vapor	mg/cm² /h	37.07	≥ 2
	Lining: water vapor coefficient	mg/cm²	297	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	ETPU/Rubber (NBR)			
	Outsole abrasion resistance (volume loss)	mm³	114	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.47	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.35	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22
	Antistatic value	MegaOhm	42.6	0.1 - 1000
	ESD value	MegaOhm	20	0.1 - 100
	Heel energy absorption	J	33	≥ 20
Toecap	Nano Carbon			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	16.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	23.0	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com