

#

###

Safety Jogger ##### ##, ## # ##, ### ##### ## ## #####.
#####.

## ##	## ## ##
## ##	##
##	SJ # ##
##	N/A
###	PU / PU
Top	##
#####	S2 / SRC
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 JPN 21.5-31 / KOR 230-310
## ##	0.552 kg
###	ASTM F2413:2018 EN ISO 20345:2011



013



```
## ##
##### ## ## ## ## ## ##
### ## ##.
```




SRC

#####. SRC ### ## ###
SRA #
SRB ### ##### ## #####.



```
## ##(WRU)
### ## ##### ##### ## # ## ###
#####.
```



#####.



#####.



```
### ##
### ## ### ##### ### ##### #####
### #####. 100##### 1### ###
## ##
```

##:
####, ##, ##, ## # ##, ##, ##

##:
##, ## ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	2.25	≥ 0.8
	##: ### ##	mg/cm²	25	≥ 15
## ##	##			
	##: ### ##	mg/cm²/h	67.6	≥ 2
	##: ### ##	mg/cm²	541	≥ 20
##	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU / PU			
	### #####(## ##)	mm³	51.7	≤ 150
	### ## ## SRA: ###	##	0.30	≥ 0.28
	## SRA# ### ##: ##	##	0.34	≥ 0.32
	### ## ## SRB: ###	##	0.19	≥ 0.13
	## SRB# ### ##: ##	##	0.22	≥ 0.18
	### ## #	###	106	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	30	≥ 20
Top	##			
	#### ## # (## # ##### 100J)	mm	N/A	N/A
	#### ## # (## # ## ## 10kN)	mm	N/A	N/A
	#### ## # (## # ## ## 200J)	mm	14.0	≥ 14
	#### ## # (## # ## ## 15kN)	mm	16.0	≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.



Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com