



MAMBA O6 HIGH

MAMBAHIGH

#####

MAMBA O6 HIGH#####ESD#####


####	####, TPU, #####
##	####
#####	SJ#####
#####	#####/###
#####	O6 / SR, SC, HI, HRO, CI, ESD
#####	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
#####	0.510 kg
##	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BRN



BLK



#####



#####HRO#
#####300#####

####:
#####, #####

#####:
#####, ####

#####:
#####

	####	####	##	EN ISO 20347
####	####, TPU, #####			
	#####	mg/cm²/h	3.9	# 0.8
	#####	mg/cm²	32.3	# 15
##	####			
	#####	mg/cm²/h	4.90	# 2
	#####	mg/cm²	41	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/###			
	#####	mm³	59	# 150
	##### - #####NaLS - #####	#####	0.46	# 0.31
	##### - #####NaLS - #####	#####	0.47	# 0.36
	SR ### - ##### - #####	#####	0.28	# 0.19
	SR##### - ##### - #####	#####	0.25	# 0.22
	####	#####	25.0	0.1 - 1000
	ESD#	#####	38	0.1 - 100
	#####	J	37	# 20

#####: 42
#####Safety Jogger #####