



MAMBA O6 HIGH

MAMBAHIGH

#####

MAMBA O6 HIGH #####

ESD-#####. ### #####,

#####


#### #####	#####
#####	#####
#####	##### SJ foam
#####	#####
#####	O6 / SR, SC, HI, HRO, CI, ESD
#####	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
### #####	0.510 kg
#####	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



BRN



BLK



#####



(HRO)

300°C.

#####:
#####, #####

##:
#####, #####

##:

#####

	#####	#####	#####	EN ISO 20347
####	####, ##, #####			
	####: #####	##/##²/#	3.9	# 0.8
	####: #####	##/##²	32.3	# 15
#####	#####			
	#####: #####	##/##²/#	4.90	# 2
	#####: #####	##/##²	41	# 20
#####	##### SJ foam			
	#####: ##### (#####/#####) (#####)	#####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	#####/#####			
	##### (#####)	##³	59	# 150
	##### - Ceramic + NaLS - #####	#####	0.46	# 0.31
	#####			
	##### - Ceramic + NaLS - #####-	#####	0.47	# 0.36
	#####			
	SR ##### - ##### + ##### - #####	#####	0.28	# 0.19
	#####			
	##### SR - ##### + ##### - #####	#####	0.25	# 0.22
	#####			
	#####	#####	25.0	0.1 - 1000
	##### (ESD)	#####	38	0.1 - 100
	#####	J	37	# 20

#####: 42

Safety Jogger, #####
#####