

MAMBAHIGH

#####


MAMBA 06 HIGH #####

#####

ESD #####

#####

#####	#####, TPU, #####
#####	#####
#####	SJ #####
#####	#####/###
#####	O6 / SR, SC, HI, HRO, CI, ESD
#####	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
#####	0.510 kg
#####	EN ISO 20347:2022+A1:2024 ASTM F2892:2024



```
#####
#####
```



BRN



BLK



(HRO)
300 °C

#####:
#####, #####

#####:
#####, #####

#####:

#####

#####	#####	#####	EN ISO 20347
#####	#####, TPU, #####		
	#####: #####	##./##./##	3.9 # 0.8
	#####: #####	##./##	32.3 # 15
#####	#####		
	#####: #####	##./##./##	4.90 # 2
	#####: #####	##./##	41 # 20
#####	SJ #####		
	#####: ##### (###/####) (###)	###	Dry 25600 cycles/Wet 12800 cycles 25600/12800
#####	#####/###		
	##### (#####)	##	59 # 150
	##### - ##### + NaLS - #####	#####	0.46 # 0.31
	##### - ##### + NaLS - #####	#####	0.47 # 0.36
	SR Slip Resistance - Ceramic + Glycerin - #####	#####	0.28 # 0.19
	##### SR - ##### + ##### - #####	#####	0.25 # 0.22
	#####	#####	25.0 0.1 - 1000
	### ESD	#####	38 0.1 - 100
	#####	##	37 # 20

#####: 42

Safety Jogger #####
#####