SAFETY JOGGER TACTICAL

Medium

MAMBA 06 LOW

MAMBALOW

lightweight, sporty and waterproof low-cut

MAMBA 06 LOW offers superior foot protection with its waterproof membrane, rubber outsole and cold insulation.

Upper	TPU, Mesh, Textile
Lining	Membrane
Footbed	SJ Recycled Foam Footbed (96% recycled)
Outsole	Phylon/Rubber (NBR)
Category	06 / SR, SC, HI, HRO, CI, ESD
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.390 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024

BRN

BLK



Rubber outsole
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Waterproof lining
Keeps your feet dry and comfortable in wet environments.

Industries:
Tactical, Uniform

Environments:
Extreme slippery surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	**TPU, Mesh, Textile**			
	Upper: permeability to water vapor	mg/cm²/h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	32.3	≥ 15
Lining	**Membrane**			
	Lining: permeability to water vapor	mg/cm²/h	4.90	≥ 2
	Lining: water vapor coefficient	mg/cm²	41	≥ 20
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800
Outsole	**Phylon/Rubber (NBR)**			
	Outsole abrasion resistance (volume loss)	mm³	59	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.46	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.47	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.28	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.25	≥ 0.22
	Antistatic value	MegaOhm	25.0	0.1 - 1000
	ESD value	MegaOhm	38	0.1 - 100
	Heel energy absorption	J	37	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.