

MAMBA 06 MID

MAMBAMID

mid-cut occupational shoe with waterproof membrane and heat-resistant outsole

MAMBA 06 MID offers superior foot protection with its waterproof membrane, rubber outsole and cold insulation.

| | - |
|------------------|---|
| Upper | TPU, Mesh, Textile |
| Lining | Membrane |
| Footbed | SJ foam footbed |
| Outsole | Phylon/Rubber (NBR) |
| Category | 06 / SR, ESD, CI, HRO |
| Size range | EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315 |
| Sample weight | 0.476 kg |
| Norms | EN ISO 20347:2022+A1:2024 |



























Keeps your feet dry and comfortable in wet environments.



Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.





Industries:

Tactical, Uniform

Environments:

Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|---------|--|-----------------------|---|--------------|
| Upper | TPU, Mesh, Textile | | | |
| | Upper: permeability to water vapor | mg/ _{Cm²} /h | 2.5 | ≥ 0.8 |
| | Upper: water vapor coefficient | $mg/_{CM^2}$ | 30 | ≥ 15 |
| Lining | Membrane | | | |
| | Lining: permeability to water vapor | $mg/_{Cm^2}/h$ | 3.5 | ≥2 |
| | Lining: water vapor coefficient | $mg/_{Cm^2}$ | 35 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| Outsole | Phylon/Rubber (NBR) | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 76.4 | ≤150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.52 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.51 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.32 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.36 | ≥ 0.22 |
| | Antistatic value | Mega0hm | 145 | 0.1 - 1000 |
| | ESD value | Mega0hm | 38 | 0.1 - 100 |
| | Heel energy absorption | J | 26 | ≥ 20 |

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



