

Medium

MODULO LEA S3S MID T

MDLCHS3SMT

Tiger Grip ### ## ### ## ##### ## ## ##### ## ### ##

```
## ### ## MODULO LEA S3S# ## ## ## ## ## ## ##
#### #### #### #####. Tiger Grip ## ## ## #### ##
#### #### ## ## #### ## #### #####. #### ## ## ####.
```

## ##	#### ## ##, ### ## ##
## ##	3D ##
###	SJ # ##
##	## ## ##
###	##, BASF PU
Top	## ##
####	S3S / SR, SC, LG, ESD, ##, CI, FO, HRO
## ##	EU 35-50
## ##	0.670 kg
###	EN ISO 20345:2022+A1:2024
	ASTM F2413:2024



```
### ## ##
## ### ### ### ## # ## #####
## ## ##### #####.
```



300°C# #### ## # ####.




```
## ##(CI)
##(CI) ##### ## ##### #####. ##
##### #####.
```



```
##(HI)
##(HI) #####
#####. ## ### ## ### #####.
```



```
## ##(LG)
#### ## # ## # ##### #### ## #####
# #### ##### #### #### #####.
```



```
## ##
### ## ##### ## #####
#####. ## ## ##### ## #
##### ## ##### ## #####.
```

##:
####, ##, ##, ##, ## # ##, ##, ##, ## # ##

##:
##, ## ##### ##, ### ##, ### ## ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ## ##, ### ## ##			
	##: ### ##	mg/cm²/h		≥ 0.8
	##: ### ##	mg/cm²		≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h		≥ 2
	##: ### ##	mg/cm²		≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##		25600/12800
###	##, BASF PU			
	### #####(## ##)	mm³		≤ 150
	## ## ## - ## + NaLS - ## ## ##	##		≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##		≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##		≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##		≥ 0.22
	### ## #	###		0.1 - 1000
	ESD #	###		0.1 - 100
	#### ## ##	J		≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm		N/A
	#### ## # (## # ## ## 10kN)	mm		N/A
	#### ## # (## # ## ## 200J)	mm		≥ 14
	#### ## # (## # ## ## 15kN)	mm		≥ 14

##:

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com