

# **MODULO DELTA 06 LOW**

**MDLODLTLOW** 

## **Waterproof Low Occupational Shoes**

MODULO DELTA 06 LOW waterproof leather shoes give workers secure grip, slip & heat resistance, and lasting protection indoors and outdoors.

	<del>-</del>
Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather
Lining	Membrane, Recycled Mesh
Footbed	SJ foam footbed
Outsole	BASF PU/Rubber (NBR)
Category	06 / SR, SC, LG, ESD, FO, HRO
Size range	EU 37-48 / UK 4.0-13.0 / US 4.5-13.5 JPN 23-31.5 / KOR 240-315
Sample weight	0.555 kg
Norms	EN ISO 20347:2022+A1:2024 ASTM F2892:2024

























#### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



## Heat resistant outsole (HRO)

The outsole resists high temperatures up to 300°C.



#### **Metal free**

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



## Waterproof (WR)

Waterproof footwear prevents liquids to enter into the shoe.



## **Electrostatic Discharge (ESD)**

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 Kilo0hm and 100 MegaOhm.

ecovadis

SEP 2025



## **Heel energy absorption**

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.





#### **Industries:**

Tactical, Uniform

#### **Environments:**

Extreme slippery surfaces, Wet environment

## **Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Upper	Abrasion Resistant Synthetic, Milled Full-Grain Leather					
	Upper: permeability to water vapor	mg/ <sub>Cm²</sub> /h	2.71	≥ 0.8		
	Upper: water vapor coefficient	$mg/_{\mathrm{CIII}^2}$	26	≥ 15		
Lining	Membrane, Recycled Mesh					
	Lining: permeability to water vapor	$mg/_{Cm^2}/h$	6.36	≥2		
	Lining: water vapor coefficient	$mg/_{\mathrm{Cm}^2}$	51	≥ 20		
Footbed	SJ foam footbed					
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	Dry 25600 cycles/Wet 12800 cycles	25600/12800		
Outsole	BASF PU/Rubber (NBR)					
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	117	≤150		
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.44	≥ 0.31		
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.42	≥ 0.36		
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.29	≥ 0.19		
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.32	≥ 0.22		
	Antistatic value	Mega0hm	28.4	0.1 - 1000		
	ESD value	Mega0hm	33	0.1 - 100		
	Heel energy absorption	J	35	≥ 20		

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.





