



 ### ## ##### ##### ## #####
 #####. ## ## ##### ### ## #
 ##### ## ##### ## #####.

##:
####, ##, ##, ## # ##, ###, ##, ##

##:
##, ### ##, ##

##:
#####. ### ##### ## ##### ## ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##, ### ## ##			
	##: ### ##	mg/cm²/h		≥ 0.8
	##: ### ##	mg/cm²		≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h		≥ 2
	##: ### ##	mg/cm²		≥ 20
###	SJ # ##			
	###: ####(##/##)(###)	##		25600/12800
###	##, BASF PU			
	### #####(## ##)	mm³		≤ 150
	## ## ## - ## + NaLS - ## ## ##	##		≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##		≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##		≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##		≥ 0.22
	### ## #	###		0.1 - 1000
	ESD #	###		0.1 - 100
	#### ## ##	J		≥ 20
Top	## ##			
	#### ## # (## # ##### 100J)	mm		N/A
	#### ## # (## # ## ## 10kN)	mm		N/A
	#### ## # (## # ## ## 200J)	mm		≥ 14
	#### ## # (## # ## ## 15kN)	mm		≥ 14

##.

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com