SAFETY JOGGER
INDUSTRIAL

Heavy

MODULO LE S3S MID TG

MDLOLEAS3M

Tiger Grip ### ### ## #### ## ### ## ### ## #####.

The MODULO LE S3S MID is a mid-cut safety boot with a full-grain leather upper. It features a heat-resistant outsole, metal-free toe cap and midsole and Tiger Grip Technology for maximum safety and comfort in challenging environments.

## ##	#### ##, ### ## ##
## ##	3D ##
###	SJ # ##
##	## ## ##
###	##, BASF PU
Top	## ##
####	S3S / SR, SC, LG, ESD, ##, CI, FO, HRO
## ##	EU 35-50 / UK 3.0-14.0 / US 3.0-15.0 JPN 21.5-33.0 / KOR 230-330
## ##	0.666 kg
###	EN ISO 20345:2022+A1:2024 ASTM F2413:2024

BLK

ESD WPA CI 3FIT SYSTEM

##
#####.

###
300°C# ### ## # ####.

##(LG)
####.

#
###, ### ## ### ## ### #### ####.

##
###. ### ## ### 100% ## ## #### ####.

Tiger Grip-##
Tiger Grip ### ### #### ##### ## ###, ### ## ###, ### ##, ### ### ### ## ##### ### ##### #####. # #### ## ## ##### ###### ## ### ## ## #### #### ######.

##:
##, ##, ##, ## # ##

##:
##, ### ##, ### ## ##, ##

##:
####. ### ###### ## #### ### ###.

	##	## ##	##	EN ISO 20345
## ##	**#### ##, ### ## ##**			
	##: ### ###	mg/cm²/h		≥ 0.8
	##: ### ##	mg/cm²		≥ 15
## ##	**3D ##**			
	##: ### ###	mg/cm²/h		≥ 2
	##: ### ##	mg/cm²		≥ 20
###	**SJ # ##**			
	###: ####(##/##)(###)	##		25600/12800
###	**##, BASF PU**			
	### ####(## ##)	mm³		≤ 150
	## ### ## - ### + NaLS - ## ### ####	##		≥ 0.31
	## ### ## - ### + NaLS - ## ## ###	##		≥ 0.36
	SR ### ## - ### + #### - #### ### ##	##		≥ 0.19
	SR ### ## - ### + #### - ## ## ###	##		≥ 0.22
	### ## #	###		0.1 - 1000
	ESD #	###		0.1 - 100
	#### ### ##	J		≥ 20
Top	**## ##**			
	#### ## #(## # ##### 100J)	mm		N/A
	#### ## #(## # ## ## 10kN)	mm		N/A
	#### ## #(## # ## ## 200J)	mm		≥ 14
	#### ## #(## # ## ## 15kN)	mm		≥ 14

##:

###, ## ## #### ### # ####. ## #### ### Safety Jogger # #### ###, ### ## ## ### ## ##### ##### ### # ####.