

MODULO PURE S3S S TG

MDLPRS3STG

Easy-to-clean, metal-free and slip-on safety shoe with anti-penetration midsole and Tiger Grip extreme grip outsole

Designed for professionals in food, healthcare, and painting, the MODULO PURE slip-on safety shoe features an easy-to-clean, stain-resistant Lorica upper and a non-marking Tiger Grip outsole for extreme grip and traction. The rotation circle on the forefoot allows smooth pivots while maintaining grip. Completely metal free and vegan.

| | • | () (et a |
|------------------|--|----------|
| Upper | Lorica | |
| Lining | 3D-Mesh | |
| Footbed | SJ foam footbed | |
| Midsole | Anti-puncture Textile | |
| Outsole | Rubber (NBR), BASF PU | WHT |
| Тоесар | Nano Carbon | |
| Category | S3S / SR, ESD, HI, CI, FO, HRO | |
| Size range | EU 35-50 | |
| Sample weight | 0.560 kg | |
| Norms | EN ISO 20345:2022+A1:2024 ASTM F2413:2024 | BLK |

Lorica

Lorica is a high-performance synthetic microfiber that offers exceptional strength and durability. It repels water, oils and stains and meets strict HACCP hygiene standards.

≶



Tiger Grip Technology

Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.



3FIT SYSTEM

Metal free

НАССР

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



EXCLUSIVE

LORICA

Electrostatic Discharge (ESD) ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Puncture resistant lightweight Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.

Rubber outsole

Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



Industries:

Assembly, Catering, Chemical, Cleaning, Food & beverages, Industry, Logistics, Medical

Environments:

Dry environment, Extreme slippery surfaces, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|---------|--|-----------------|---|--------------|
| Upper | Lorica | | | |
| | Upper: permeability to water vapor | mg/cm²/h | 1.80 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm² | 17 | ≥ 15 |
| Lining | 3D-Mesh | | | |
| | Lining: permeability to water vapor | mg/cm²/h | 18.2 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm² | 146.8 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance (dry/wet) (cycles) | cycles | Dry 25600 cycles/Wet 12800 cycles | 25600/12800 |
| Outsole | Rubber (NBR), BASF PU | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 124 | ≤ 150 |
| | Basic Slip resistance - Ceramic + NaLS - Forward heel slip | friction | 0.38 | ≥ 0.31 |
| | Basic Slip resistance - Ceramic + NaLS - Backward forepart slip | friction | 0.45 | ≥ 0.36 |
| | SR Slip resistance - Ceramic + glycerin - Forward heel slip | friction | 0.23 | ≥ 0.19 |
| | SR Slip resistance - Ceramic + glycerin - Backward forepart slip | friction | 0.26 | ≥ 0.22 |
| | Antistatic value | MegaOhm | 57.1 | 0.1 - 1000 |
| | ESD value | MegaOhm | 69 | 0.1 - 100 |
| | Heel energy absorption | J | 32 | ≥ 20 |
| Toecap | Nano Carbon | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | N/A | N/A |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | N/A |
| | Impact resistance toecap (clearance after impact 200J) | mm | 17.0 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 23.0 | ≥ 14 |

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace



INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP