



# SAFETY JOGGER

## INDUSTRIAL



Medium

## RUSH S3

**Fashionable safety shoe with a zipper on the side**

Safety Jogger's RUSH safety shoes offer supreme protection with a steel toecap and midsole. Antistatic, oil & fuel resistant, and breathable for comfort in various industries and environments.

Upper	Crazy Horse Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Category	S3 / SR, SC, CI, FO
Size range	EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 JPN 22.5-31.5 / KOR 235-315
Sample weight	0.712 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024



SND



BRN



CAM



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.




### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm




### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Steel midsole

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.

Industries:

Automotive, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry

Environments:

Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Crazy Horse Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	7.8	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	68	≥ 15
Lining	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm²/h	46.42	≥ 2
	Lining: water vapor coefficient	mg/cm²	372	≥ 20
Footbed	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>PU/PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	88	≤ 150
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	friction	0.38	≥ 0.31
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	friction	0.45	≥ 0.36
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	friction	0.34	≥ 0.19
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	friction	0.31	≥ 0.22
	Antistatic value	MegaOhm	21.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	28	≥ 20
Toecap	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



www.safetyjogger.com