



Medium

SANDY S3S MID TLS

SANDYS3MTL

TLS # # # ##### # # # # # # #####.


S3S TLS# ##, ## # ##### # # # #####. ##### # ##, ## # ##, SR # # ##### # ####. ## TLS # # ##, ## # # #, ## # # # ESD # # # #####.

## ##	##### ##
## ##	##
##	SJ # # # #
##	# # # #
###	# # # # #
Top	##
####	S3S / SR, ESD, ##, CI, FO, HRO
## ##	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0
	JPN 21.5-31 / KOR 230-310
## ##	0.610 kg
## ##	ASTM F2413:2018
	EN ISO 20345:2022+A1:2024



TLS(#### # # #)

Safety Jogger # #### TLS # #
#####. #
#, # # #####
#####. # # ##### TLS ##### # #
#####. #
#####.



#

ESD# ## ##### # # # #

#####. # # ##### 100#####
100##### #####.




SJ # # #

#####. # # # ##### #####. # #
100# #####.



#

#####.



#

#####, # # # # #,
#####, #, # # # # #

#####.



##(SR)

SRA+SRB=SRC # #
#####. SR# # # ##### # # #
#####.



SND

##:

####, ####, ##, ##

##:

##, ## ##### ##, ## ##, ####

##:

####. #### ##### ## #### ## ####.

	##	## ##	##	EN ISO 20345
## ##	##### ##			
	##: #### ##	mg/cm ² /h	5.44	≥ 0.8
	##: #### ##	mg/cm ²	48	≥ 15
## ##	##			
	##: #### ##	mg/cm ² /h	86.31	≥ 2
	##: #### ##	mg/cm ²	691	≥ 20
##	SJ #### ## ##			
	##: #####(##/##)(##)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## ##	####/##			
	##: #####(## ##)	mm ³	128	≤ 150
	## ## - ## + NaLS - ## ## ####	##	0.43	≥ 0.31
	## ## - ## + NaLS - ## ## ##	##	0.44	≥ 0.36
	SR ## - ## + #### - #### ## ##	##	0.36	≥ 0.19
	SR ## - ## + #### - ## ## ##	##	0.33	≥ 0.22
	## ## #	###	37.2	0.1 - 1000
	ESD #	###	19	0.1 - 100
	##### ## ##	J	30	≥ 20
Top	##			
	##: #### ## ## ## ## ## 100J)	mm	N/A	N/A
	##: #### ## ## ## ## 10kN)	mm	N/A	N/A
	##: #### ## ## ## ## ## 200J)	mm	18.5	≥ 14
	##: #### ## ## ## ## ## 15kN)	mm	23.0	≥ 14

##:

####, ## ## #### ## ## ## ##. ## ##### #### Safety Jogger # ##### ##, #### ## ## #### ## #### ## ## ##.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com