



Medium

## SAFETYBOY WINTER S1P

SFTYBOYWNT

**Economically priced winter boot with teddy lining.**

The SAFETYBOY WINTER S1 is a versatile, economically priced winter boot with teddy lining, offering warmth, antistatic properties, non-marking outsole, removable footbed, and heel energy absorption. Ideal for various industries and harsh work conditions.

Upper	Barton Action Leather
Lining	Teddy
Footbed	Teddy
Midsole	Steel
Outsole	PU
Toecap	Steel
Category	S1 P / SRC, CI
Size range	EU 35-48 / UK 3.0-13.0 / US 3.0-13.5 JPN 21.5-31.5 / KOR 230-315
Sample weight	0.620 kg
Norms	ASTM F2413:2018 EN ISO 20345:2011



BLK



### Warm lining

Keeps your feet warm and dry in cold environments.



### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



### Non-marking outsole

Non-marking outsoles do not leave color marks on the ground.



### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

Industries:

Assembly, Construction, Industry, Food & beverages, Logistics

Environments:

Cold environment, Extreme slippery surfaces, Dry environment, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	<b>Barton Action Leather</b>			
	Upper: permeability to water vapor	mg/cm²/h	1.18	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	15	≥ 15
Lining	<b>Teddy</b>			
	Lining: permeability to water vapor	mg/cm²/h	83.25	≥ 2
	Lining: water vapor coefficient	mg/cm²	666	≥ 20
Footbed	<b>Teddy</b>			
	Footbed: abrasion resistance (dry/wet) (cycles)	cycles	25600/12800	25600/12800
Outsole	<b>PU</b>			
	Outsole abrasion resistance (volume loss)	mm³	78	≤ 150
	Outsole slip resistance SRA: heel	friction	0.35	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	46.8	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	33	≥ 20
Toecap	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	N/A
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	N/A
	Impact resistance toecap (clearance after impact 200J)	mm	18.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.5	≥ 14

Sample size:

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED  
IN EUROPE

www.safetyjogger.com