



SAFETY JOGGER

INDUSTRIAL



#

SPEEDY S3S

###

SR ### ### ### ###, ### ## ## ### ### ## ###
#####. ### ### ### ### # ### ### ###, ###, ### # ## ###
#####.

##

3D

SJ #

##

PU/##

Top ##

S3S / SR, ##, CI, FO, HRO

EU 36-47 / UK 3.5-12.0 / US 4.0-13.0

JPN 22.5-31 / KOR 235-310

0.683 kg

ASTM F2413:2018

EN ISO 20345:2022



SJ ###

#####. # ### # #####. ##
100%# #####.



SRC

#####. SRC ### ## ##
SRA #
SRB ### ## ## ## ## ## ##.



###

300°C# ### ## # #####.



#

#####. #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

##:
###, ##, ##, ##, ##

##:
##, ### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	## ## ##			
	##: ### ##	mg/cm²/h	3.9	≥ 0.8
	##: ### ##	mg/cm²	38.4	≥ 15
## ##	3D ##			
	##: ### ##	mg/cm²/h	69.43	≥ 2
	##: ### ##	mg/cm²	555	≥ 20
###	SJ # ##			
	###: #####(##/##)(###)	##	25600/12800	25600/12800
###	PU/##			
	### #####(## ##)	mm³	93	≤ 150
	## ## ## - ## + NaLS - ## ## ##	##	0.55	≥ 0.31
	## ## ## - ## + NaLS - ## ## ##	##	0.44	≥ 0.36
	SR ## ## - ## + ##### - ##### ## ##	##	0.34	≥ 0.19
	SR ## ## - ## + ##### - ## ## ##	##	0.23	≥ 0.22
	### ## #	###	280.1	0.1 - 1000
	ESD #	###	N/A	0.1 - 100
	#### ## ##	J	30	≥ 20
Top	##			
	#### ## #(## # ##### 100J)	mm	N/A	N/A
	#### ## #(## # ## ## 10kN)	mm	N/A	N/A
	#### ## #(## # ## ## 200J)	mm	16.5	≥ 14
	#### ## #(## # ## ## 15kN)	mm	19.0	≥ 14

##:
###, ## ## ##### ## # #####. ## ##### ### Safety Jogger # ##### ###, ### ## ## ## ## ##### ##### ## # #####.



Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com