



#####

TOPSKATE S3S LOW

TOPSKATS3L

#####S3S#####

#####S3#####
#####

#####, #####

#####

SJ#####

#####

#####/###

#####

S3S / SR, FO, HI, HRO, CI, ESD

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.520 kg

EN ISO 20345:2022+A1:2024

ASTM F2413:2024



148




BLU



DGR



LGR



#####

#####



#####ESD#

ESD#####

###100 KiloOhm##100 MegaOhm
#####



#####

#####100#####



#####HI#

#####HI#####
#####



#####CI#

#####CI#####
##



#####

#####

####:
##, ###, #####, #####, #####, #####, #####, #####

#####:
#####, #####, ###

#####:
#####

	####	####	##	EN ISO 20345
####	#####, #####			
	#####	mg/cm²/h	10.6	# 0.8
	#####	mg/cm²	90.7	# 15
##	#####			
	#####	mg/cm²/h	31.08	# 2
	#####	mg/cm²	249	# 20
####	SJ#####			
	#####	####	Dry 25600 cycles/Wet 12800 cycles	25600/12800
#####	####/#			
	#####	mm³	133	# 150
	##### - #####NaLS - #####	####	0.43	# 0.31
	##### - #####NaLS - #####	####	0.39	# 0.36
	SR ### - ##### - #####	####	0.26	# 0.19
	SR##### - ##### - #####	####	0.26	# 0.22
	####	####	31.2	0.1 - 1000
	ESD#	####	29	0.1 - 100
	#####	J	30	# 20
#####	#####			
	#####100J#	mm	N/A	N/A
	#####10kN#####	mm	N/A	N/A
	#####200J#	mm	19.0	# 14
	#####15kN#	mm	25.0	# 14

#####: 42

#####Safety Jogger #####