



#

TOPSKATE S3S LOW

TOPSKATS3L

####, ## # #### ## # S3S ### #####

##, ## # ## # ## #, ##, #### ##### S3 #####.

##,

##

SJ ### #

##

###/##

Top #####

S3S / SR, FO, HI, HRO, CI, ESD

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5
JPN 21.5-31.5 / KOR 230-315

0.520 kg

EN ISO 20345:2022+A1:2024
ASTM F2413:2024



148




BLU



DGR



LGR



##

#####. ## ## ##### ## # #####
#####.



##

ESD# ## ##### # ## #####
#####. ##
100##### 100### #####.



##

##.
100% ## ## #####.



##(HI)

##(HI) ##### ## ## ##
#####. ## ## ## ## #####.



##(CI)

##(CI) ##### ## #####. ##
#####.



##

##.

##:
####, ##, ##, ##, ##, ####, ## # ##, ## # ##

##:
##, #### ##, ##

##:
#####. ### ##### ## ##### ### ##.

	##	## ##	##	EN ISO 20345
## ##	#### ##, ##			
	##: ### ###	mg/cm²/h	10.6	# 0.8
	##: ### ##	mg/cm²	90.7	# 15
## ##	### ##			
	##: ### ###	mg/cm²/h	31.08	# 2
	##: ### ##	mg/cm²	249	# 20
##	SJ ### # ###			
	###: ####(##/##)(###)	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
## #	###/##			
	### #####(## ##)	mm³	133	# 150
	## ### ## - ### + NaLS - ## ### #####	##	0.43	# 0.31
	## ### ## - ### + NaLS - ## ## ###	##	0.39	# 0.36
	SR ### ## - ### + ##### - ##### ## ##	##	0.26	# 0.19
	SR ### ## - ### + ##### - ## ## ###	##	0.26	# 0.22
	### ## #	###	31.2	0.1 - 1000
	ESD #	###	29	0.1 - 100
	#### ## ##	J	30	# 20
Top	####			
	#### ## ##(## # ## 100J)	mm	N/A	N/A
	#### ## ##(## # ## ## 10kN)	mm	N/A	N/A
	#### ## ##(## # ## ## 200J)	mm	19.0	# 14
	### ## ## ##(## # ## ## 15kN)	mm	25.0	# 14

#: 42

##, ## ## ##### ## # #####. ## ##### ## Safety Jogger # ##### ##, ### ## ## ##### ## ##### ##### ## # #####.