



#

TOPSKATE S3S LOW

TOPSKATS3L

S3S

S3

#####,

#####

SJ

#####

##/####

###

S3S / SR, FO, HI, HRO, CI, ESD

EU 35-48 / UK 3.0-13.0 / US 3.0-13.5

JPN 21.5-31.5 / KOR 230-315

0.520 kg

EN ISO 20345:2022+A1:2024

ASTM F2413:2024



148




BLU



DGR



LGR



####

#####

#####




####(ESD)

ESD#####

#####10###35 #

#####



####

100%#####

###



####HI#

####HI#####

##



####CI#

####CI#####

###



####

#####

##:
##, ##, ##, ##, ##, ##, #####, ##

##:
#####, ####, ####

####:
#####

##		####	##	EN ISO 20345
##	####, ####			
	#####	##/####/##	10.6	#### 0.8
	#####	##/####	90.7	#### 15
##	#####			
	#####	##/####/##	31.08	#### 2
	#####	##/####	249	#### 20
##	SJ #####			
	#####/#####	##	Dry 25600 cycles/Wet 12800 cycles	25600/12800
##	##/####			
	#####	## ³	133	#### 150
	##### - ## + NaLS - #####	##	0.43	#### 0.31
	##### - ## + NaLS - #####	##	0.39	#### 0.36
	SR ## - ## + ## - #####	##	0.26	#### 0.19
	SR ## - ## + ## - #####	##	0.26	#### 0.22
	####	##	31.2	0.1 - 1000
	ESD#	##	29	0.1 - 100
	####	J	30	#### 20
	###			
##	#####100J#	##	N/A	N/A
	#####10kN#	##	N/A	N/A
	#####200J#	##	19.0	#### 14
	#####15kN#	##	25.0	#### 14

####: 42

#####Safety Jogger#####